

Black pigment FEPREN BP-600 A

MANUFACTURER / SELLER

PRECHEZA a.s.
 Nábřeží Dr. E. Beneše 24
 751 62 Přerov, Czech Republic
 tel.: + 420 581 706 831
 fax: + 420 581 706 830
precheza@precheza.cz
www.precheza.cz

PRODUCT INFORMATION

Chemical substance	Iron oxide (Fe ₃ O ₄)
Grade	standard milled black pigment
Basic properties	very high tinting-strength, hiding power, is not affected by alkalis and proves high lightfastness and weather resistance is up to 110°C
Classification	ISO 1248:B III 3 a EC TARIC code 28211000
Colour Index No.	77499
CAS No.	1317-61-9
EINECS No.	215-277-5
Delivery form	powder
Packaging	25 ± 0.2 kgs paper bags or according agreement
Storing	original packaging, dry and covered stores, pile up max. 3 pallets

Preservation of processing properties six months from the date of expedition is guaranteed by the supplier

RECOMMENDED APPLICATION

Colouring of concrete products like roof tiles, terrazzo, colour floor tiles.

CAN BE ALSO APPLIED FOR

Colouring of cement-based mixtures.
 The pigment is not intended for paint producers but application in this sector is possible after successful trial tests of the end-user.

Information on application is given in good faith and does not constitute any guarantee.

We recommend trial application tests.

TECHNICAL DATA	Unit	Value	Testing method
Fe ₂ O ₃ content	(%)	min. 90.0	SPTM:LM/FE.1
Volatile matters at 105°C	(%)	max. 1.5	SPTM:LM/FE.4
Specific conductivity	(µS/cm)	max. 1500	SPTM:LM/FE.6
pH of aqueous extract		min. 5.0	SPTM:LM/FE.7
Colour shade		according to agreed sample	SPTM:LM/FE.10

Safety Data Sheet is available on www.precheza.cz